

## IWTaT

### Ambient Temperature Wireless Transmitter



- *Measures ambient temperature*
- *High accuracy*
- *Choice of enclosure types*
- *Long battery life*
- *User selectable update rates*
- *Based on IEC 802.15 protocol*

#### DESCRIPTION

The IWTaT ambient temperature transmitter has been designed to operate with the range of wireless receivers manufactured by Cynergy3.

Either ambient temperature alone or both temperature and humidity measurements can be specified. Typically the unit transmits the measured values back to a IWR-PORT which can be connected to an Ethernet or RS232/485 communications network. For temperature and humidity see the IWTRhT.

The unit is specially designed to maximise battery life and in a typical application the battery life can exceed two years.

#### Enclosure Styles

<b>Style</b>	Industrial Head
<b>Orientation</b>	Any
<b>Wall/Ceiling Mounting</b>	2 x 3mm screws
<b>Enclosure Size</b>	85mm dia x 57mm deep
<b>Weight</b>	Approx 70g



#### Technical Specifications

Parameter	Min	Typ	Max	Comments
Supply Voltage		3.6V		Battery Powered
Supply Current (mA)			40	When transmitting data
Battery Life		100kΩ		Dependent on upgrade rate
Ambient Temperature Range	-40°C		80°C	
Relative Humidity Range	0%		100%	
Temperature Accuracy		±0.5°C		At 30°C
Relative Humidity Accuracy		±3%		Between 10 and 90% RH

#### Ordering Information

Please supply  
**Part Number:** IWTaT